

LEGM600BH120L2H7

IGBT Power Module

Features

- $V_{CE}=1200V$ $I_C=600A$
- Low $V_{CE(sat)}$
- V_{CEsat} with positive temperature coefficient
- Maximum junction temperature 175°C
- Isolation Type Package


Applications

- Inverter for motor drive
- AC and DC servo drive amplifier
- Uninterruptible power supply

Package Type & Internal Circuit



L2



Internal Circuit

Maximum Rated Values (IGBT Inverter)

Symbol	Parameter	Conditions	Ratings	Unit
V_{CES}	Maximum Power Dissipation	$V_{CE}=0V, I_C=1mA, T_{vj}=25^{\circ}C$	1200	V
I_C	Continuous Collector Current	$T_C=100^{\circ}C$	600	A
I_{CRM}	Peak Collector Current	$I_{CRM}=2I_C$	1200	A
V_{GES}	Gate-Emitter Voltage	$T_{vj}=25^{\circ}C$	± 20	V
P_{tot}	Total Power Dissipation	$T_C=25^{\circ}C, T_{vjmax}=175^{\circ}C$	3260	W

Maximum Rated Values (IGBT Inverter)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=600\text{ A}, V_{GE}=15\text{ V}, T_{vj}=25\text{ }^{\circ}\text{C}$		1.9		V
		$I_C=600\text{ A}, V_{GE}=15\text{ V}, T_{vj}=150\text{ }^{\circ}\text{C}$		2.3		V
$V_{GE(th)}$	Gate Threshold Voltage	$I_C=6.0\text{ mA}, V_{CE}=V_{GE}, T_{vj}=25\text{ }^{\circ}\text{C}$	5.3	5.7	6.2	V
I_{CES}	Collector-Emitter Cut-off Current	$V_{CE}=1200\text{ V}, V_{GE}=0\text{ V}, T_{vj}=25\text{ }^{\circ}\text{C}$			5	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{CE}=0\text{ V}, V_{GE}=15\text{ V}, T_{vj}=25\text{ }^{\circ}\text{C}$			400	nA
$t_{d(on)}$	Turn-on Delay Time, Inductive Load	$I_C=600\text{ A}, V_{CE}=600\text{ V}$ $V_{GE}=\pm 15\text{ V}$ $R_G=10\text{ }\Omega$ $T_{vj}=25\text{ }^{\circ}\text{C}$		852		ns
t_r	Rise Time, Inductive Load			672		ns
$t_{d(off)}$	Turn-off Delay Time, Inductive Load			2202		ns
t_f	Fall Time, Inductive Load			150		ns
E_{on}	Turn-on Energy Loss per Pulse			328		mJ
E_{off}	Energy Loss per Pulse			111		mJ
$t_{d(on)}$	Turn-on Delay Time, Inductive Load	$I_C=600\text{ A}, V_{CE}=600\text{ V}$ $V_{GE}=\pm 15\text{ V}$ $R_G=10\text{ }\Omega$ $T_{vj}=150\text{ }^{\circ}\text{C}$		801		ns
t_r	Rise Time, Inductive Load			763		ns
$t_{d(off)}$	Turn-off Delay Time, Inductive Load			2375		ns
t_f	Fall Time, Inductive Load			133		ns
E_{on}	Turn-on Energy Loss per Pulse			374		mJ
E_{off}	Energy Loss per Pulse			133		mJ
R_{thJC}	Thermal resistance, junction to case	per IGBT			0.046	K/W
$T_{vj\text{ op}}$	Temperature under switching conditions		-40		150	$^{\circ}\text{C}$
I_{sc}	SC	$V_{GE}\leq 15\text{ V}, V_{CE}=600\text{ V},$ $t_p\leq 6\text{ }\mu\text{s}, T_{vj}=150\text{ }^{\circ}\text{C},$ $V_{CEmax}=V_{CES}-L_{sCE}\cdot di/dt$		2100		A

Maximum Rated Values (Diode Inverter)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	$T_{vj}=25\text{ }^{\circ}\text{C}$		1200		V
I_F	Continuous DC Forward Current	$T_C=100\text{ }^{\circ}\text{C}$		600		A
I_{FRM}	Repetitive Peak Forward Current	$t_p=1\text{ ms}$		1200		A


Characteristic Values (Diode Inverter)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
V_F	Forward Voltage	$I_F=600\text{ A}, V_{CE}=0\text{ V}, T_{vj}=25\text{ }^{\circ}\text{C}$		1.78		V
		$I_F=600\text{ A}, V_{CE}=0\text{ V}, T_{vj}=150\text{ }^{\circ}\text{C}$		1.86		V
I_{rr}	Peak reverse recovery current	$I_F=600\text{ A}, V_R=600\text{ V}$ $-di/dt=550\text{ A/us}$ $T_{vj}=25\text{ }^{\circ}\text{C}$		60		A
Q_r	Recovered Charge			22.5		uC
E_{rec}	Reverse Recovery Energy			5.35		mJ
I_{rr}	Peak reverse recovery current	$I_F=600\text{ A}, V_R=600\text{ V}$ $-di/dt=550\text{ A/us}$ $T_{vj}=150\text{ }^{\circ}\text{C}$		88		A
Q_r	Recovered Charge			50.8		uC
E_{rec}	Reverse Recovery Energy			11.7		mJ
R_{thJC}	Thermal resistance, junction to case	per Diode			0.092	K/W
$T_{vj\text{ op}}$	Operating Junction Temperature		-40		150	$^{\circ}\text{C}$

Module Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
V_{isol}	Isolation voltage	$t=1\text{ min}, f=50\text{ Hz}$	2500			V
T_{stg}	Storage Temperature		-40		125	$^{\circ}\text{C}$
M_t	Module Electrodes Torque	Recommended(M6)	2.5		5.0	N·m
M_s	Module-to-Sink Torque	Recommended(M6)	3.0		6.0	N·m
G	Weight of Module			340		g

(Dimensions in Millimeters)



DISCLAIMER

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.